PRODUCT STOPS PNEUMATIC ROLLER AND BLADE STOPS (POWER CONV. ONLY)



Pneumatic power conveyor stops are used where automatic line control is required such as accumulation, indexing, inspection stations, etc. This stop is normally used on variable pressure accumulators and live roller conveyors.

SPECIFY MODEL NUMBER PER EXAMPLE

PRSL-196VP-33

(pneumatic)(roller or blade stop*)(left or right**)-(conveyor type)-(between frames) *Specify RS for roller stop; BS for blade stop. **Specify L for left hand; R for right hand.

SPECIFICATIONS

ROLLER STOP: 1.9" dia. x 16 ga. steel roller, model 196S.

BLADE STOP: 7 ga. formed angle.

AIR CYLINDER: Double action. (60-80 PSI) required.

SOLENOID VALVE: Single.

BEARINGS: Removable type, heavy duty ball bearing, with cast iron housings.

OPTIONAL: Double solenoid and electrical controls.

WIDTHS: 24 hour shipments include 15", 19", 21", 25", 27", 33" and 39" BF. Medium duty models above 39" BF, light duty models in 10", 16" and 22" BF and heavy duty models above 39" BF are 2 week shipment.

■ 24 hour shipment ■ 2 week shipment

MANUAL ROLLER AND BLADE STOPS (POWER CONV. ONLY)



Manual operated power conveyor stops are hand operated and used where line control is required such as accumulation, indexing, inspection stations, etc. This stop is normally used on variable pressure accumulators and live roller conveyors.

SPECIFY MODEL NUMBER PER EXAMPLE

MBSR-196LR-21

(manual)(roller or blade stop*)(left or right**)-(conveyor type)-(between frames) *Specify RS for roller stop; BS for blade stop. **Specify L for left hand; R for right hand.

SPECIFICATIONS

ROLLER STOP: 1.9" dia. x 16 ga. steel roller, model 196S.

BLADE STOP: 7 ga. formed angle.

BEARINGS: Removable type, heavy duty ball bearing, with cast iron housings.

LOCK: Spring loaded catch.

WIDTHS: 24 hour shipments include 15", 19", 21", 25", 27", 33" and 39" BF. Medium duty models above 39" BF, light duty models in 10", 16" and 22" BF and



heavy duty models above 39" BF are 2 week shipment.